



Specification Sheet

Rite-On®

Special Multi-Purpose EP Grease



Benefits

- New formula
- Stable performance over a wide temperature range
- Resistant to water washout
- Higher dropping point
- High pressure protection
- Protects against rust and corrosion
- New packaging
- Greater Timken Load
- Excellent pump ability
- Resists shear down

Description

Rite-On is a superior, extreme pressure lithium grease compounded with highly refined conventional base oils. It is a versatile grease that provides excellent lubrication in nearly any application. Rite-On resists structural and consistency changes, even under periods of high temperature and pressure. It will consistently deliver superior performance.

Performance. Value. Longevity.

Applications

Recommended for use in:

- Auto, truck, and bus lubrication
- Agricultural and construction equipment
- Industrial applications

Part Numbers

#040881 10 tube/cs.

#040832 120 lbs.

Typical Operating Temperature Range

+10°F – +250°F

Specifications

Lithium	
NL GI Grade	#2
Dropping Point, °F (ASTM D-217)	585
Base Oil Viscosity, cSt 40°C (ASTM D-445)	220
Base Oil Viscosity, cSt 100°C (ASTM D-445)	15
Timken OK Load, lbs.	60
Four Ball Extreme Pressure (ASTM D-2596) Weld Point, kgf Load Wear Index	315 45
Four Ball Wear Test Scar Diameter, mm (ASTM D-2266)	0.54
Water Washout, wt% loss at 175°F 10% max wt loss (ASTM D-1264)	3.8
Rust and Corrosion (ASTM D-1743)	Pass