



Specification Sheet

Rite-On®

Multi-Purpose EP Grease



Benefits

- Stable performance over a wide temperature range
- Resistant to water washout
- High pressure protection
- Protects against rust and corrosion
- Excellent pump ability
- Resists shear down

Description

Rite-On is an extreme pressure lithium grease compounded with highly refined conventional base oils. It is a versatile grease that provides excellent lubrication in nearly any application. Rite-On resists structural and consistency changes, even under periods of high temperature and pressure. It will consistently deliver superior performance.

Applications

Recommended for use in:

- Auto, truck, and bus lubrication
- Agricultural and construction equipment
- Industrial applications

Part Numbers

#40857	single tube (14 oz.)
#40881	10 tube/cs.
#40873	40 tube/cs.
#40832	120 lbs.

Typical Operating Temperature Range

+10°F – +250°F

Specifications

Lithium	
NL GI Grade	#2
Dropping Point, °F (ASTM D-217)	383
Base Oil Viscosity, cSt 40°C (ASTM D-445)	173
Base Oil Viscosity, cSt 100°C (ASTM D-445)	16
Timken OK Load, lbs.	50
Four Ball Extreme Pressure (ASTM D-2596)	
Weld Point, Kg	250
Load Wear Index	46
Four Ball Wear Test Scar Diameter, mm (ASTM D-2266)	0.55
Water Washout, wt% loss at 175°F 10% max wt loss (ASTM D-1264)	4.7
Rust and Corrosion (ASTM D-1743)	Pass