

Safety Data Sheet CONKLIN COMPANY, INC.

Date Prepared: 1/2/2023 SDS Number: 4058

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier	General Use		
Spunflex & Spunflex II Fabric	Polyester Roof Material		
Manufacturer's Name	Emergency Telephone Numbers		
Conklin Company	Health: (888) 786-0974 Transport: (800) 424-9300		
Address (Number, Street, City, State and Zip)	Phone Number for Additional Information		
551 Valley Park Drive	(952) 445-6010		
Shakopee, MN 55379	Website: www.conklin.com		

SECTION 2 - HAZARDS IDENTIFICATION

Hazard statements: No label element(s) required

Precautions: No label element(s) required

Response: No label element(s) required

Potential Health Effects, Based on Individual Components (May Vary Among Individuals)

Skin: Not expected to cause irritation under normal use. **Not expected to cause irritation under normal use. Ingestion:** Not expected to cause irritation under normal use. **Inhalation:** Not expected to cause irritation under normal use.

Medical conditions aggravated by exposure:

None known

Chronic effect No information available.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Number	Percent by Weight		
No known OSHA Hazardous Ingredients				
See Section 8 for exposure guidelines.				

SECTION 4 - FIRST AID MEASURES

EYES: Do not rub eye(s). Let the eye(s) water naturally for a few minutes. Have victim look right and left, then up and down. If particle/dust does not dislodge, gently flush with clean, lukewarm, gently flowing water for 5 minutes or until particle/dust is removed, while holding the eyelid(s) open. If irritation persists, immediately obtain medical attention. DO NOT attempt to manually remove anything stuck to the eye.

SKIN: No health effects expected. If irritation does occur, flush with lukewarm water, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.

INGESTION: If irritation or discomfort occurs, obtain medical advice.

INHALATION: If symptoms are experienced, remove source of contamination or move victim to fresh air. Obtain medical advice.

Date Prepared: 1/2/2023 Page 2 of 3
Spunflex & Spunflex II Fabric SDS Number: 4058

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: Not applicable.

EXINGUISHING MEDIA: Water fog or spray, dry chemical, foam, carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES: Use water, dry chemical, CO2, or foam, as appropriate for

surrounding fire. This is an organic material that may burn.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURE: Collect for reuse, recycling, or proper disposal.

SECTION 7 - HANDLING AND STORAGE

STORAGE TEMPERATURE: Store above 40°F and below 100°F.

HANDLING AND STORAGE PRECAUTIONS: Store in dry, cool area away from open flames,

sparks, or oxidizers.

SECTION 8 - PERSONAL PROTECTION/EXPOSURE CONTROLS

ENGINEERING CONTROLS: Provide sufficient general and local exhaust ventilation to maintain safe exposure levels. Take measures to minimize exposure. Provide a source of clean water for flushing eves and skin.

EYE PROTECTION REQUIREMENTS: Use ANSI-approved eye protection (e.g. safety glasses, goggles), as required by work conditions. Use ANSI-approved chemical splash goggles and face shield if splashing may occur.

SKIN PROTECTION REQUIREMENTS: Chemical-resistant gloves and clothing, as needed, to prevent skin contact. Wash hands before eating, drinking, or smoking.

RESPIRATORY PROTECTION: Not required in normal uses.

AIRBORNE EXPOSURE LIMITS

	OSHA	ACGIH	
Components	PEL/TWA	TLV/TWA	STEL

Definitions:

PEL = Permissible Exposure Limit

TLV = Threshold Limit Value

TWA = Time-weighted average (8 hour day)

STEL = Short term exposure limit (15 minutes), no more than 60 min./day

(c) = Ceiling (not to be exceeded under any condition)

(s) = Skin

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Formed Sheets Solubility in Water: Insoluble Color: White/Black Specific Gravity (Water = 1): Not available Odor: None Evaporation Rate (Butyl Acetate = 1): Not applicable Boiling Range: Not Applicable Vapor Pressure (mm Hg): Not applicable pH: Not applicable Vapor Density (Air = 1): Not applicable

VOC: Not applicable

SECTION 10 – REACTIVITY

Stability: Stable under anticipated storage and handling conditions.

Hazardous Polymerization: Will not occur.

Incompatibilities (Materials to Avoid): Avoid strong oxidizers and excessive heat. Hazardous Decomposition Products: Carbon monoxide and carbon dioxide.

Date Prepared: 1/2/2023 Page 3 of 3
Spunflex & Spunflex II Fabric SDS Number: 4058

SECTION 11 - TOXICOLOGICAL INFORMATION

Product not tested as a whole. Refer to Section 3 for potential health effects.

SECTION 12 - ECOLOGICAL INFORMATION

Non-hazardous. Dispose as solid waste.

SECTION 13 - DISPOSAL CONSIDERATIONS

Non-hazardous. Dispose as solid waste.

SECTION 14 - TRANSPORTATION INFORMATION

Not a DOT Hazardous Material.

SECTION 15 - REGULATORY INFORMATION

No information available.

SECTION 16 - OTHER INFORMATION

This document replaces the 1/2/2020 version. All Safety Data Sheets reviewed for composition and regulatory status.

The information contained in this Safety Data Sheet is based on data available to us from suppliers, and is believed to be true and correct; however, Conklin makes no warranty, express or implied, regarding the accuracy of this data or results obtained from the use of this product. Conklin and its employees assume no responsibility for injury or damage from the use of this product.