



Safety Data Sheet
CONKLIN COMPANY, INC.

Date Prepared: 6/29/2022

SDS Number: 3011

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier Luboil® (Liquid)	General Use Multipurpose lubricant
Manufacturer's Name Conklin Company	Emergency Telephone Numbers Health: (888) 786-0974 Transport: (800) 424-9300
Address (Number, Street, City, State and Zip) 551 Valley Park Drive Shakopee, MN 55379	Phone Number for Additional Information (952) 445-6010 Website: www.conklin.com

SECTION 2 - HAZARDS IDENTIFICATION

Signal Word:	Warning
Hazard statements:	<p>Harmful if swallowed or inhaled. Aspiration hazard: May be fatal if swallowed and enters airways. May be absorbed through skin. Causes serious eye irritation. Causes skin irritation. Flammable liquid and vapor. May cause cancer, see Proposition 65 statement.</p>

Precautions: Keep away from heat, sparks, pilot lights, open flames, static electricity, or other sources of heat or ignition. - No smoking.
 Ground/Bond container and receiving equipment.
 Use explosion-proof equipment when handling.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing mist, vapors and spray.
 Use only outdoors or in a well ventilated area.
 Do not eat, drink or smoke when using this product.
 Wear gloves, safety glasses or goggles, and long-sleeved clothing when handling.
 Wash hands thoroughly after handling.
 Keep container tightly closed.

Response: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice or attention.
 If swallowed: Immediately call a physician or Poison Control Center.
 Rinse Mouth.
 If on skin or hair: Immediately take off all contaminated clothing. wash skin with soap and water.
 If skin irritation occurs: Get medical advice or attention.
 Wash contaminated clothing before reuse.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 Immediately call a physician or Poison Control Center.
 In case of fire: Use foam, dry chemical or CO2 to extinguish.

Potential Health Effects, Based on Individual Components (May Vary Among Individuals)**Eye:** Liquid, fumes, mists, or vapors may cause irritation.**Skin:** May cause irritation.**Ingestion:** May cause moderate irritation to mouth, throat, and stomach, along with nausea and vomiting.**Inhalation:** May cause irritation to respiratory tract (mouth, nose, throat and lungs).

Causes damage to Blood, Central Nervous System, Digestive System, Eyes, Gastrointestinal Tract, Gingival Tissue, Heart, Kidneys, Liver, Lungs, Respiratory System, Skeleton, Skin, and Spleen through prolonged or repeated exposure.

Medical conditions aggravated by exposure:

None known

Chronic effect Carcinogenicity: Contains Ethylbenzene (IARC-2B).
IARC-2B = The chemical is possibly carcinogenic to humans.
See Section 15 for California Proposition 65 information.**SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS Number	Percent by Weight
Heavy Naphthenic Petroleum Oil	64742-52-5	40% to 50%
Polybutene	9003-29-6	20% to 30%
Xylene	1330-20-7	10% to 20%
White Mineral Oil	8042-47-5	5% to 10%
Ethylbenzene	100-41-4	1% to 5%
Paraffin wax	Proprietary	1% to 5%
Monochlorotoluene	25168-05-2	1% to 5%
Petrolatum (petroleum),oxidized, Bu este	90669-48-0	1% to 5%

See Section 8 for exposure guidelines.

SECTION 4 - FIRST AID MEASURES**EYES:** Quickly and gently blot or brush chemical off the face. Immediately flush the contaminated eye(s) with clean, lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens until after flushing is complete. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.**SKIN:** Remove contaminated clothing, shoes, and leather goods (e.g. watchbands, belts). Quickly and gently, blot or brush away excess chemical. Wash gently and thoroughly with lukewarm, gently flowing water and non-abrasive soap for 5 minutes. If irritation persists, repeat flushing. Obtain medical advice. Completely decontaminate clothing, shoes, and leather goods before reuse, or discard.**INGESTION:** Never give anything by mouth to a victim who is rapidly losing consciousness, is unconscious, or is convulsing. Have victim rinse mouth thoroughly with water. Do NOT induce vomiting. Have victim drink a glass of water (2 to 8 ounces or 60 to 240 mL). Immediately obtain medical attention.**INHALATION:** If symptoms are experienced, remove source of contamination or move victim to fresh air. Obtain medical advice.**SECTION 5 - FIRE FIGHTING MEASURES****FLASH POINT:** 113°F**EXINGUISHING MEDIA:** Foam, dry chemical, CO2.**SPECIAL FIRE FIGHTING PROCEDURES:** Limit use of water spray to cool containers and to protect personnel. Water may not be effective to extinguish a fire involving this material. Vapors are heavier than air and may be ignited after traveling considerable distances, causing flashback or explosion. Firefighters should use approved self-contained breathing apparatus and full turn-out (Bunker) gear when fighting fires involving chemicals, to protect against possible toxic fumes or vapors. Cool and use caution when approaching fire-exposed containers.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURE: Use personal protection recommended in Section 8. Remove all sources of ignition, including sparks and static electricity. Use non-sparking, explosion-proof tools and equipment. Do not vacuum. Ventilate area thoroughly. Stay upwind. Isolate area from unprotected personnel. Dike to prevent spill from spreading. Collect with compatible absorbent material and place in metal container with tight fitting cover. Floor may be slippery - use care and clean thoroughly. Keep out of sewer, septic system, ground water, and open waters. Notify federal, state and local authorities, as applicable.

SECTION 7 - HANDLING AND STORAGE

STORAGE TEMPERATURE: Store above 40°F and below 100°F.

HANDLING AND STORAGE PRECAUTIONS: Use personal protection recommended in Section 8. Do not cut, weld, drill, or otherwise expose empty or full containers to heat, sparks, pilot lights, open flames, static electricity, or other sources of heat or ignition. Open containers slowly in case of pressure accumulation. Bond and ground containers and equipment during transfer. Vapors are/may be heavier than air and may cause ignition away from storage or handling location. Use non-sparking tools. Protect from direct sunlight. Store in dry, cool, ventilated area in tightly closed containers out of the reach of children. Do not store on side. Avoid creasing or impacting container sidewalls. Empty containers may be hazardous. Do not eat, drink, or smoke in chemical use or storage areas. Wash hands after handling and before eating, drinking, or smoking. Do not rub eyes with soiled hands. See Section 10 for metals or other materials to avoid.

SECTION 8 - PERSONAL PROTECTION/EXPOSURE CONTROLS

ENGINEERING CONTROLS: Provide sufficient general and local explosion-proof exhaust ventilation to maintain safe exposure levels. Take measures to minimize exposure. Provide a source of clean water for flushing eyes and skin.

EYE PROTECTION REQUIREMENTS: Use ANSI-approved eye protection (e.g. safety glasses, goggles), as required by work conditions. Use ANSI-approved chemical splash goggles and face shield if splashing may occur.

SKIN PROTECTION REQUIREMENTS: Chemical-resistant gloves and clothing, as needed, to prevent skin contact. Wash hands before eating, drinking, or smoking.

RESPIRATORY PROTECTION: To protect against inhalation, a NIOSH-approved air-purifying respirator with organic vapor cartridges and dust/mist pre-filters may be permissible. Use a dust/mist filter or pre-filter if spraying. Use a positive pressure air-supplied respirator for unknown or uncontrolled situations, or when air-purifying respirators may not provide adequate protection.

AIRBORNE EXPOSURE LIMITS

Components	OSHA PEL/TWA	ACGIH TLV/TWA	STEL
Xylene	TWA 100 ppm (435 mg/m ³)		150 ppm
White Mineral Oil	TWA 5 mg/m ³		
Ethylbenzene	TWA 100 ppm (435 mg/m ³)	TWA 20 ppm	125 ppm

Definitions:

PEL = Permissible Exposure Limit

TLV = Threshold Limit Value

TWA = Time-weighted average (8 hour day)

STEL = Short term exposure limit (15 minutes), no more than 60 min./day

(c) = Ceiling (not to be exceeded under any condition)

(s) = Skin

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Form:	Liquid	Solubility in Water:	Insoluble
Color:	Clear, amber	Specific Gravity (Water = 1):	0.89 - 0.90
Odor:	Petroleum	Evaporation Rate (Butyl Acetate = 1):	< 1
Boiling Range:	Not determined	Vapor Pressure (mm Hg):	Not determined
pH:	Not applicable	Vapor Density (Air = 1):	> 1
VOC:	16.8% by weight		

SECTION 10 – REACTIVITY

Stability: Stable under anticipated storage and handling conditions.

Hazardous Polymerization: Will not occur.

Incompatibilities (Materials to Avoid): Avoid strong oxidizers and excessive heat.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and hydrogen chloride.

SECTION 11 - TOXICOLOGICAL INFORMATION

Refer to Section 3 for potential health effects.

For Heavy Naphthenic Petroleum Oil: Acute Oral toxicity (LD50): > 5000 mg/kg (rat)

Acute Dermal toxicity (LD50): >2000 mg/kg (rabbit)

Acute Inhalation toxicity (LC50): >2500 mg/m³/4h (rat).

For Monochlorotoluene: Acute Oral toxicity (LD50): 3600 mg/kg (rat)

Acute Inhalation toxicity (LC50): 34 g/m³/2h (mouse).

For White Mineral Oil: Acute Oral toxicity (LD50): > 5000 mg/kg (rat)

Acute Dermal toxicity (LD50): >2000 mg/kg (rabbit).

(Testing not done on behalf of Conklin.)

SECTION 12 – ECOLOGICAL INFORMATION

Product not tested as a whole. Refer to Section 6 for information regarding accidental releases. Keep out of trash, water, sewer, and drainage systems.

SECTION 13 - DISPOSAL CONSIDERATIONS

Recycle or dispose of contents and empty containers according to federal, state and local regulations. Keep out of trash, water, sewer, and drainage systems. Oils and solvents may be recycled, incinerated, or fuel blended at an EPA-permitted facility.

SECTION 14 - TRANSPORTATION INFORMATION

UN1993, Flammable liquids, n.o.s. (Petroleum Distillates), 3, III

Exceptions: DOT Not Regulated, Combustible liquid, flash point > 100°F

Not packaged for Air or Vessel Transport

For additional information, please call the Transportation Department at (952) 445-6010.

SECTION 15 - REGULATORY INFORMATION

California Proposition 65 statement:

WARNING: This product can expose you to chemicals including Cumene (< 780 ppm), Ethylbenzene (1% to 5%), which are known to the State of California to cause cancer; and Toluene (< 780 ppm), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

This product contains the following chemical(s) subject to the reporting requirements of SARA Title III, Section 313 (40 CFR Part 372): Xylene: 10% to 20%; Ethylbenzene: 1% to 5%.
CERCLA RQ = 100 lbs (Xylene); CERCLA RQ = 1000 lbs (Ethylbenzene).

SECTION 16 - OTHER INFORMATION

This document replaces the 1/2/2020 version. Health and safety information reviewed.

The information contained in this Safety Data Sheet is based on data available to us from suppliers, and is believed to be true and correct; however, Conklin makes no warranty, express or implied, regarding the accuracy of this data or results obtained from the use of this product. Conklin and its employees assume no responsibility for injury or damage from the use of this product.