

OUTPOST®

TPO Bonding Adhesive

CONKLIN®

ROOFING
SYSTEMS

PRODUCT DESCRIPTION

OUTPOST bonding adhesive is designed for bonding TPO membranes and flashing to horizontal and vertical roof substrates.

APPLICATION INSTRUCTIONS

- Apply adhesive to the membrane and substrate which are clean, dry, and free of debris. Apply at the rate of 120 square feet per gallon per surface, sufficient to bond 60 square feet of membrane in place.
- Apply adhesive using a solvent-resistant 3/8" medium nap roller.
- Allow adhesive to partially dry (approximately 5-10 minutes) to a tacky feel when touched with the back side of a dry finger before bonding membrane to substrate.
- Mate the membrane to the substrate avoiding any air entrapment and apply pressure by means of a roller or push broom to assure complete bonding.
- Apply only when the temperature is at least 50°F and rising.

SHELF LIFE AND STORAGE

The shelf life of an unopened container of this adhesive stored at temperatures between 60°F (15.6°C) and 95°F (35°C) is 1 year from the date of manufacture. Store out of direct sunlight in a cool, well-ventilated area. Avoid storing the container directly on the floor or against an outside wall or near heat sources. Protect from freezing.

OUTPOST TPO Bonding Adhesive

KEEP OUT OF REACH OF CHILDREN.

FOR PROFESSIONAL OR INDUSTRIAL USE ONLY, USE ONLY WITH APPROVED EQUIPMENT.

REFER TO THE PRODUCT DATA SHEET AND SAFETY DATA SHEET FOR DETAILED INFORMATION.

ATTENTION:

- Empty containers remain hazardous until all flammable vapor, which may explode upon ignition, are gone from residue and container. Observe all labeled hazard precautions.
- Do not cut, puncture, or weld while hazard exists. Do not reuse empty containers. Dispose of according to all federal, state, and local regulations.

STORAGE: Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Protect from sunlight.

DISPOSAL: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national, and/or international regulation.

DANGER: 

HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. SUSPECTED OF CAUSING CANCER. SUSPECTED OF DAMAGING FERTILITY OF UNBORN CHILD. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

Keep away from heat, sparks, pilot lights, open flames, static electricity, or other sources of heat or ignition. No smoking. Use explosion-proof equipment when handling. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, vapors and spray. Use only outdoors or in a well ventilated area. Do not eat, drink, or smoke when using this product. Wear gloves, safety glasses, or goggles, and long-sleeved clothing when handling. Wash hands thoroughly after handling. Keep container tightly closed.

FIRST AID: If in eyes: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice or attention. If swallowed: immediately call a physician or Poison Control Center. Rinse mouth. If on skin or hair: immediately take off all contaminated clothing. Wash skin with soap and water. If skin irritation occurs: get medical advice or attention. Wash contaminated clothing before reuse. If inhaled: remove person to fresh air and keep comfortable for breathing. In case of fire: use foam, dry chemical or CO2 to extinguish.

 **CALIFORNIA WARNING:** Cancer risk from Ethylbenzene. Reproductive harm from Toluene. See www.P65Warnings.ca.gov.

VOC: 641 g/L EPA Method 24 VOC

