

# FLEECE BACKED

Waterborne Bonding Adhesive

**CONKLIN**<sup>®</sup>

**ROOFING  
SYSTEMS**

## PRODUCT DESCRIPTION

Fleece Backed Waterborne Bonding Adhesive is designed for bonding Conklin's fleece backed single-ply membranes to horizontal and vertical surfaces. NOT FOR USE WITH SMOOTH BACKED OUTPOST TPO.

## APPLICATION INSTRUCTIONS

- Only apply when ambient temperature is 50°F and rising. Make sure the substrate surface is clean and free of debris.
- Apply adhesive to the substrate only at a rate of 140-180 square feet per gallon for smooth backed Flexion 2.0. For fleece backed membranes, apply adhesive at rate of 100-120 square feet per gallon. The coverage rate depends on the porosity of the substrate.
- Apply adhesive using a 3/8" medium nap roller.
- Fleece backed membrane: Roll the fleece backed membrane onto the adhesive coated substrate immediately after applying the adhesive avoiding any air entrapment. Do not allow adhesive to dry. Membrane must be rolled into the wet adhesive.
- Apply pressure with a heavy roller to assure bonding.
- For vertical applications (smooth backed Flexion 2.0 only) apply adhesive onto both membrane and substrate at the rate of 175-200 square feet per gallon. For porous surfaces such as concrete apply a light coating of adhesive as a seal coat. Allow to dry to finger tack and then roll membrane onto the substrate. Apply pressure to complete bond.

## SHELF LIFE AND STORAGE

The shelf life for an unopened container, stored between 60°F and 80°F out of direct sunlight, is 1 year from date of manufacture.

**KEEP OUT OF REACH OF CHILDREN.**

**FOR PROFESSIONAL OR INDUSTRIAL USE ONLY, USE ONLY WITH APPROVED EQUIPMENT.**

**REFER TO THE PRODUCT DATA SHEET AND SAFETY DATA SHEET FOR DETAILED INFORMATION.**

## ATTENTION

- Empty containers remain hazardous until all flammable vapor, which may explode upon ignition, are gone from residue and container. Observe all labeled hazard precautions.
- Do not cut, puncture, or weld while hazard exists. Do not reuse empty containers. Dispose of according to all federal, state, and local regulations.

## STORAGE

Keep from freezing! Do not store below 40°F. Keep out of direct sunlight.

## DISPOSAL

Dispose of containers in accordance with Federal, State, and Local regulations.



**COMBUSTIBLE LIQUID. MAY DAMAGE FERTILITY OR THE UNBORN CHILD. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, pilot lights, open flames, static electricity, or other sources of heat or ignition. No smoking. Avoid breathing mist, vapors, and spray. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. Wear gloves, safety glasses or goggles, and long-sleeved clothing when handling. Wash hands, forearms, and face thoroughly after handling. Keep container tightly closed. Store locked up, in a well-ventilated space. In case of fire: Use media other than water to extinguish.

## FIRST AID

If in eyes: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice or attention. If swallowed: immediately call a physician or Poison Control Center. Rinse mouth. If on skin or hair: immediately take off all contaminated clothing. Wash skin with soap and water. If skin irritation occurs: get medical advice or attention. Wash contaminated clothing before reuse. If inhaled: remove person to fresh air and keep comfortable for breathing. In case of fire: use foam, dry chemical or CO2 to extinguish.

Causes damage to eyes through prolonged or repeated exposure.

## CALIFORNIA WARNING

Cancer risk and reproductive harm from Ethylene oxide.  
See [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**VOC:** 179 g/L

**Net Contents: 5 gallons (18.93l)**

**Conklin Company Inc.**  
**Roofing Systems Division**  
551 Valley Park Drive  
Shakopee, MN 55379  
[www.ConklinRoofingSystems.com](http://www.ConklinRoofingSystems.com)