

WAC II®

High Strength Weathered Acrylic Roof Cleaner

Manufacturer:

Conklin Company Inc.
551 Valley Park Drive
Shakopee, Minnesota 55379
(800) 888 – 8838 Fax (952) 496 - 4285

Product Description:

Basic use: WAC II® is a unique, highly effective cleaner designed specifically for cleaning Conklin weathered acrylic roof coatings and approved membranes. See: Membrane Coating Specification.

Limitations: When using WAC II, it is important to thoroughly remove ALL dirt, grease, chalk and debris and any remaining WAC II residue prior to applying coatings. Best results are obtained by wetting the roof surface with water prior to cleaning. The use of a stiff bristle broom may be needed to scrub extremely dirty areas such as low spots.

Sizes: WAC II is available in 5-gallon containers and 55-gallon drums.

Coverage Rate: Coverage rates will vary depending on roof condition. WAC II should yield approximately 400-500 square feet per gallon.

Application:

WAC II should be applied at full strength with a brush, roller, and conventional airless or portable tank sprayer. The cleaner is designed to be applied at full strength – DO NOT DILUTE. Once applied, allow the cleaner to remain on the roof surface for a minimum of 20 minutes prior to water rinse, i.e., with high-pressure spray. Make sure to remove all residues and let roof surface dry thoroughly.

Storage:

Keep product from freezing.

Disposal:

Dispose of product in accordance with local, state, and federal regulation.

Safety:

Warning: HARMFUL OR FATAL IF SWALLOWED. CONTACT A PHYSICIAN IMMEDIATELY. CORROSIVE. MAY CAUSE BURNS. Keep out of the reach of children. Avoid contact with plants, shrubs and grass. Use in well-ventilated areas, and close container after each use.

First Aid: Eyes and skin – immediately flush with plenty of water for at least 15 minutes. Ingestion – if swallowed, **DO NOT INDUCE VOMITING**, dilute with three to four glasses of water or milk. Immediately call a Poison Control Center or physician for further instructions. Inhalation – immediately move to fresh air.

Contains: Sodium Silicate Liquid (CAS #1344-09-8) and Sodium Tripolyphosphate (CAS #77758-29-4)

For US Health Hazard Information, call:

1-888-786-0974

Proposition 65 Statement: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

VOC Concentration: as applied (less water and exempt solvents): **0 g/L** (0 lbs./gal.)

