

Tack Coat™

Primer for Approved Roofing Membranes

Manufacturer:

Conklin Company Inc.
551 Valley Park Drive
Shakopee, Minnesota 55379
(800) 888 – 8838 Fax (952) 496 - 4285

Product Description:

Basic use: Tack Coat™, when used in conjunction with WAC II®, effectively prepares aged roofing membranes to receive base coat and top coat of Conklin's Rapid Roof III and Equinox elastomeric roof coating.

Limitations: Must not be applied at temperatures below 40°F or during inclement weather. Surface temperature must be at least 5°F above dew point and relative humidity less than 80 percent to ensure dry surfaces. Mix thoroughly before use. Ambient temperature should not exceed 100°F and surface temperature should not exceed 120°F. Conklin's Tack Coat must not be used on surfaces that have not been thoroughly cleaned with WAC II according to manufacturer's specifications.

Sizes: Available in 5-gallon containers and 55-gallon drums

Coverage Rate: Coverage rates will vary depending on roof condition. Tack Coat should yield approximately 250-300 sq. ft. per gallon.

Companion Products:

- Rapid Roof® III acrylic latex roof coating
- Equinox® acrylic latex roof coating

UL790: See UL listings for use as an optional primer

Application:

Conklin Tack Coat should be applied at full strength with a brush, roller, conventional airless sprayer or portable tank sprayer. Tack Coat must be thoroughly mixed with a drill-mounted jiffy mixer (55 gallon drum) prior to application. The primer is clear as it is applied and when it has properly dried. Drying time is approximately 2-8 hours depending on temperature and humidity. If too much primer is applied or the primer is exposed to moisture before it has properly cured, the primer will become milky white and will need additional drying time.

Clean Up:

Clean tools promptly with a warm water solution of Mox® multipurpose cleaner.

Disposal:

Dispose of product in accordance with local state and federal regulations governing hazardous waste.

Tack Coat™

Primer for Approved Roofing Membranes

Safety:

Warning: COMBUSTIBLE. VAPOR HARMFUL – VERY IRRITATING TO RESPIRATORY SYSTEM. CAUSES SEVERE EYE AND SKIN IRRITATION. HARMFUL IF SWALLOWED. Keep out of the children. Keep away from heat, sparks and open flames during storage and use. Do not breathe dust or mist – use only in well-ventilated areas, and close container after each use. Avoid prolonged or repeated contact with skin.

First Aid: Eyes – immediately flush with plenty of water for at least 15 minutes, and seek immediate medical attention. Skin – wash with large amounts of soap and water, and seek a physician if irritation persists. Ingestion – if swallowed, **DO NOT INDUCE VOMITING**, dilute with three to four glasses of water. Immediately call a Poison Control Center or physician for further instructions. Inhalation – immediately move to fresh air. Seek medical attention if respiratory irritation persists. For US Health Hazard Information, call:

1-888-786-0974

Contains: Butoxythanol (CAS #111-76-2), Butyl Alcohol (CAS #71-36-3) and Talc (CAS #14807-96-6)

Proposition 65 Statement: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Storage:

Keep product from freezing and away from open flame or sparks.

Please Note: *Previous field-applied coatings and residential properties are not warrantable.*



©Conklin Company Inc. 2017
003142017