



Safety Data Sheet CONKLIN COMPANY, INC.

Date Prepared: 1/3/18

SDS Number: 4102

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier Activate LS	General Use Silicone Roof Coating
Manufacturer's Name Conklin Company	Emergency Telephone Numbers Health: (888) 786-0974 Transport: (800) 424-9300
Address (Number, Street, City, State and Zip) 551 Valley Park Drive Shakopee, MN 55379	Phone Number for Additional Information (952) 445-6010 Website: www.conklin.com

SECTION 2 - HAZARDS IDENTIFICATION



Signal Word:	Danger
Hazard statements:	Combustible liquid and vapor. Harmful if swallowed or inhaled. Solvents may be absorbed through skin. Causes skin irritation and eye irritation.

Precautions: Keep away from heat, sparks, pilot lights, open flames, static electricity, or other sources of heat or ignition. - No smoking.
Ground/Bond container and receiving equipment.
Use explosion-proof equipment when handling.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing mist, vapors and spray.
Use only outdoors or in a well ventilated area.
Do not eat, drink or smoke when using this product.
Wear gloves, safety glasses or goggles, and long-sleeved clothing when handling.
Wash hands thoroughly after handling.
Keep container tightly closed.

Response: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Get medical advice or attention.
If swallowed: Immediately call a physician or Poison Control Center.
Rinse Mouth.
If on skin or hair: Immediately take off all contaminated clothing. wash skin with soap and water.
If skin irritation occurs: Get medical advice or attention.
Wash contaminated clothing before reuse.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Immediately call a physician or Poison Control Center.
In case of fire: Use foam, dry chemical or CO2 to extinguish.

Potential Health Effects, Based on Individual Components (May Vary Among Individuals)

- Eye:** Fumes, mists, or vapors may cause irritation. Liquids can cause serious irritation.
- Skin:** May cause irritation. Prolonged exposure may cause skin sensitization.
- Ingestion:** Harmful if swallowed. May cause mouth, throat and stomach irritation. If swallowed, product may cause aspiration hazard with possible lung damage.
- Inhalation:** May cause moderate irritation to respiratory tract (mouth, nose, throat and lungs).

Medical conditions aggravated by exposure:

None known

Chronic effect Not known to contain component(s) at 0.1% or greater listed as a carcinogen or possible carcinogen.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Number	Percent by Weight
Nepheline Syenite	37244-96-5	35 to 45%
Liquid Silicone Polymer	Proprietary	20 to 30%
Distillates (petroleum), hydrotreated light	64742-47-8	20% to 30%
Titanium Dioxide	13463-67-7	5 to 15%
2-Butanone,O,O', O''-(Methylsilyldiylne)Trioxime	22984-54-9	2 to 7%
Silica, Amorphous, fumed, crystal-free	112945-52-5	1 to 3%

See Section 8 for exposure guidelines.

SECTION 4 - FIRST AID MEASURES

EYES: Quickly and gently blot or brush chemical off the face. Immediately flush the contaminated eye(s) with clean, lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens until after flushing is complete. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.

SKIN: As quickly as possible, remove contaminated clothing, shoes, and leather goods (e.g. watchbands, belts). Quickly and gently, blot or brush away excess chemical. Wash gently and thoroughly with lukewarm, gently flowing water and non-abrasive soap for 5 minutes. If irritation persists, repeat flushing. Obtain medical advice. Store contaminated clothing in a manner to prevent spontaneous combustion. Completely decontaminate clothing, shoes, and leather goods before reuse, or discard.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing difficulty continues.

SECTION 5 - FIRE FIGHTING MEASURES**FLASH POINT:** 102°F**EXINGUISHING MEDIA:** Foam, dry chemical, CO2.

SPECIAL FIRE FIGHTING PROCEDURES: Limit use of water spray to cool containers and to protect personnel. Water may not be effective to extinguish a fire involving this material. Vapors are heavier than air and may be ignited after traveling considerable distances, causing flashback or explosion. Firefighters should use approved self-contained breathing apparatus and full turn-out (Bunker) gear when fighting fires involving chemicals, to protect against possible toxic fumes or vapors. Cool and use caution when approaching fire-exposed containers.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURE: Use personal protection recommended in Section 8. Remove all sources of ignition, including sparks and static electricity. Use non-sparking, explosion-proof tools and equipment. Do not vacuum. Ventilate area thoroughly. Stay upwind. Isolate area from unprotected personnel. Dike to prevent spill from spreading. Collect with compatible absorbent material and place in metal container with tight fitting cover. Floor may be slippery - use care and clean thoroughly. Keep out of sewer, septic system, ground water, and open waters. Notify federal, state and local authorities, as applicable.

SECTION 7 - HANDLING AND STORAGE

STORAGE TEMPERATURE: 40° to 80°F

HANDLING AND STORAGE PRECAUTIONS: Use personal protection recommended in Section 8. Do not cut, weld, drill, or otherwise expose empty or full containers to heat, sparks, pilot lights, open flames, static electricity, or other sources of heat or ignition. Open containers slowly in case of pressure accumulation. Bond and ground containers and equipment during transfer. Vapors are/may be heavier than air and may cause ignition away from storage or handling location. Use non-sparking tools. Protect from direct sunlight. Store in dry, cool, ventilated area in tightly closed containers out of the reach of children. Do not store on side. Avoid creasing or impacting container sidewalls. Empty containers may be hazardous. Do not eat, drink, or smoke in chemical use or storage areas. Wash hands after handling and before eating, drinking, or smoking. Do not rub eyes with soiled hands. See Section 10 for metals or other materials to avoid. Spontaneous combustion can occur from heat generation with rags.

SECTION 8 - PERSONAL PROTECTION/EXPOSURE CONTROLS

ENGINEERING CONTROLS: Provide sufficient general and local explosion-proof exhaust ventilation to maintain safe exposure levels. Take measures to minimize exposure. Provide a source of clean water for flushing eyes and skin.

EYE PROTECTION REQUIREMENTS: Use ANSI-approved eye protection (e.g. safety glasses, goggles), as required by work conditions. Use ANSI-approved chemical splash goggles and face shield if splashing may occur.

SKIN PROTECTION REQUIREMENTS: Chemical-resistant gloves and clothing, as needed, to prevent skin contact. Wash hands before eating, drinking, or smoking.

RESPIRATORY PROTECTION: To protect against inhalation, a NIOSH-approved air-purifying respirator with organic vapor cartridges and dust/mist pre-filters may be permissible. Use a dust/mist filter or pre-filter if spraying. Use a positive pressure air-supplied respirator for unknown or uncontrolled situations, or when air-purifying respirators may not provide adequate protection.

AIRBORNE EXPOSURE LIMITS

Components	OSHA PEL/TWA	ACGIH TLV/TWA	STEL
Distillates (petroleum), hydrotreated light	TWA 5 mg/m ³	10 mg/m ³	
Titanium Dioxide* *as dust	TWA 15 mg/m ³	10 mg/m ³	

Definitions:

- PEL = Permissible Exposure Limit
- TLV = Threshold Limit Value
- TWA = Time-weighted average (8 hour day)
- STEL = Short term exposure limit (15 minutes), no more than 60 min./day
- (c) = Ceiling (not to be exceeded under any condition)
- (s) = Skin

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Form:	Viscous liquid	Solubility in Water:	Not available
Color:	White	Specific Gravity (Water = 1):	Not available
Odor:	Petroleum/solvent	Evaporation Rate (Butyl Acetate = 1):	Not available
Boiling Range:	Not available	Vapor Pressure (mm Hg):	Not available
pH:	Not available	Vapor Density (Air = 1):	Not available

SECTION 10 – REACTIVITY

Stability:	Stable under anticipated storage and handling conditions.
Hazardous Polymerization:	Will not occur.
Incompatibilities (Materials to Avoid):	Avoid strong oxidizers, such as chlorine, open flames, sparks and excessive heat.
Hazardous Decomposition Products:	Carbon monoxide, carbon dioxide, and nitrogen oxides.

SECTION 11 - TOXICOLOGICAL INFORMATION

Product not tested as a whole. Refer to Section 3 for potential health effects.

SECTION 12 – ECOLOGICAL INFORMATION

Product not tested as a whole. Refer to Section 6 for information regarding accidental releases. Keep out of trash, water, sewer, and drainage systems.

SECTION 13 - DISPOSAL CONSIDERATIONS

Recycle or dispose of contents and empty containers according to federal, state and local regulations. Keep out of trash, water, sewer, and drainage systems. Oils and solvents may be recycled, incinerated, or fuel blended at an EPA-permitted facility.

SECTION 14 - TRANSPORTATION INFORMATION

US Ground (DOT)

Non-Regulated when shipped ground or rail with U.S.A.UN1993, Flammable Liquid, n.o.s., PG III

Not packaged for Air Transport

For additional information, please consult Conklin's Document Library at <http://www.conklin.com/library/index.cfm> or call the Transportation Department at (952) 445-6010.

SECTION 15 - REGULATORY INFORMATION

California Proposition 65 statement: This product does NOT contain chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.
Does not contain any chemicals subject to the reporting requirements of SARA Title III, Section 313 (40 CFR Part 372) above de minimis concentrations.

SECTION 16 - OTHER INFORMATION

This document replaces the 6/30/17 version. All Safety Data Sheets reviewed for composition and regulatory status.

The information contained in this Safety Data Sheet is based on data available to us from suppliers, and is believed to be true and correct; however, Conklin makes no warranty, express or implied, regarding the accuracy of this data or results obtained from the use of this product. Conklin and its employees assume no responsibility for injury or damage from the use of this product.