



**Safety Data Sheet**  
**CONKLIN COMPANY, INC.**

Date Prepared: 1/9/2026

SDS Number: 3026

**SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Identifier</b> Trans-Last®	<b>General Use</b> Automatic Transmission Fluid Conditioner
<b>Manufacturer's Name</b> Conklin Company	<b>Emergency Telephone Numbers</b> Health: (888) 786-0974 Transport: (800) 424-9300
<b>Address (Number, Street, City, State and Zip)</b> 551 Valley Park Drive Shakopee, MN 55379	<b>Phone Number for Additional Information</b> (952) 445-6010 <b>Website:</b> www.conklin.com

**SECTION 2 - HAZARDS IDENTIFICATION**

<b>Hazard statements:</b> Not classified.
---

**Precautions:** Not applicable.**Response:** Not applicable.**Potential Health Effects, Based on Individual Components (May Vary Among Individuals)****Eye:** Not applicable.**Skin:** Not applicable.**Ingestion:** Not applicable.**Inhalation:** Not applicable.**Medical conditions aggravated by exposure:**

None known

**Chronic effect** Not known to contain component(s) at 0.1% or greater listed as a carcinogen or possible carcinogen.**SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS Number	Percent by Weight
Proprietary	Proprietary	30% to 60%
Paraffinic petroleum distillate, hydrotreated light	64742-55-8	15% to 40%
Distillates, hydrotreated heavy paraffinic	64742-54-7	15% to 40%
Dibutylhydrogen phosphite	1809-19-4	1% to 5%

Actual concentration is withheld as a trade secret. See Section 8 for exposure guidelines.

**SECTION 4 - FIRST AID MEASURES****EYES:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses.**SKIN:** Wash with soap and water. Get medical attention if symptoms occur. Launder contaminated clothing before reuse.**INGESTION:** Treat symptomatically. Get medical attention.**INHALATION:** Remove exposed person to fresh air if adverse effects are observed

## SECTION 5 - FIRE FIGHTING MEASURES

**FLASH POINT:** > 200°F

**EXINGUISHING MEDIA:** Foam, dry chemical, CO<sub>2</sub>.

**SPECIAL FIRE FIGHTING PROCEDURES:** Limit use of water spray to cool containers and to protect personnel. Water may not be effective to extinguish a fire involving this material. Vapors are heavier than air and may be ignited after traveling considerable distances, causing flashback or explosion. Firefighters should use approved self-contained breathing apparatus and full turn-out (Bunker) gear when fighting fires involving chemicals, to protect against possible toxic fumes or vapors. Cool and use caution when approaching fire-exposed containers.

---

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**SPILL OR LEAK PROCEDURE:** Use personal protection recommended in Section 8. Remove all sources of ignition, including sparks and static electricity. Use non-sparking, explosion-proof tools and equipment. Do not vacuum. Ventilate area thoroughly. Stay upwind. Isolate area from unprotected personnel. Dike to prevent spill from spreading. Collect with compatible absorbent material and place in metal container with tight fitting cover. Floor may be slippery - use care and clean thoroughly. Keep out of sewer, septic system, ground water, and open waters. Notify federal, state and local authorities, as applicable.

---

## SECTION 7 - HANDLING AND STORAGE

**STORAGE TEMPERATURE:** Store above 40°F and below 100°F.

**HANDLING AND STORAGE PRECAUTIONS:** Use personal protection recommended in Section 8. Do not cut, weld, drill, or otherwise expose empty or full containers to heat, sparks, pilot lights, open flames, static electricity, or other sources of heat or ignition. Open containers slowly in case of pressure accumulation. Bond and ground containers and equipment during transfer. Vapors are/may be heavier than air and may cause ignition away from storage or handling location. Use non-sparking tools. Protect from direct sunlight. Store in locked, dry, cool, ventilated area in tightly closed containers out of the reach of children. Do not store on side. Avoid creasing or impacting container sidewalls. Empty containers may be hazardous. Do not eat, drink, or smoke in chemical use or storage areas. Wash hands after handling and before eating, drinking, or smoking. Do not rub eyes with soiled hands. See Section 10 for metals or other materials to avoid.

---

## SECTION 8 - PERSONAL PROTECTION/EXPOSURE CONTROLS

**ENGINEERING CONTROLS:** Provide sufficient general and local explosion-proof exhaust ventilation to maintain safe exposure levels. Take measures to minimize exposure. Provide a source of clean water for flushing eyes and skin.

**EYE PROTECTION REQUIREMENTS:** Use ANSI-approved eye protection (e.g. safety glasses, goggles), as required by work conditions. Use ANSI-approved chemical splash goggles and face shield if splashing may occur.

**SKIN PROTECTION REQUIREMENTS:** Chemical-resistant gloves and clothing, as needed, to prevent skin contact. Wash hands before eating, drinking, or smoking.

**RESPIRATORY PROTECTION:** To protect against inhalation, a NIOSH-approved air-purifying respirator with organic vapor cartridges and dust/mist pre-filters may be permissible. Use a dust/mist filter or pre-filter if spraying. Use a positive pressure air-supplied respirator for unknown or uncontrolled situations, or when air-purifying respirators may not provide adequate protection.

## AIRBORNE EXPOSURE LIMITS

Components	OSHA PEL/TWA	ACGIH TLV/TWA	STEL
Paraffinic petroleum distillate, hydrotreated light	TWA 5 mg/m <sup>3</sup> as oil mist, if generated	TWA 5 mg/m <sup>3</sup> as oil mist, if generated	10 mg/m <sup>3</sup> as oil mist, if generated
Distillates, hydrotreated heavy paraffinic	TWA 5 mg/m <sup>3</sup> as oil mist, if generated	TWA 5 mg/m <sup>3</sup> as oil mist, if generated	10 mg/m <sup>3</sup> as oil mist, if generated

### Definitions:

PEL = Permissible Exposure Limit

TLV = Threshold Limit Value

TWA = Time-weighted average (8 hour day)

STEL = Short term exposure limit (15 minutes), no more than 60 min./day

(c) = Ceiling (not to be exceeded under any condition)

(s) = Skin

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Form:	Liquid, > 200 cst @ 40°C	Solubility in Water:	Insoluble
Color:	Clear to slightly hazy, amber	Specific Gravity (Water = 1):	0.90 - 0.91
Odor:	Solvent	Evaporation Rate (Butyl Acetate = 1):	< 1
Boiling Range:	Not determined	Vapor Pressure (mm Hg):	Not determined
pH:	Not applicable	Vapor Density (Air = 1):	> 1
VOC:	0% by weight	Particle Characteristics:	Liquid, not applicable

## SECTION 10 – REACTIVITY

Stability: Stable under anticipated storage and handling conditions.

Hazardous Polymerization: Will not occur.

Incompatibilities (Materials to Avoid): Avoid strong oxidizers and excessive heat.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and nitrogen oxides.

## SECTION 11 - TOXICOLOGICAL INFORMATION

Product not tested as a whole. Refer to Section 3 for potential health effects.

## SECTION 12 – ECOLOGICAL INFORMATION

Product not tested as a whole. Refer to Section 6 for information regarding accidental releases. Keep out of trash, water, sewer, and drainage systems.

## SECTION 13 - DISPOSAL CONSIDERATIONS

Recycle or dispose of contents and empty containers according to federal, state and local regulations. Keep out of trash, water, sewer, and drainage systems. Oils and solvents may be recycled, incinerated, or fuel blended at an EPA-permitted facility.

## SECTION 14 - TRANSPORTATION INFORMATION

Not a DOT Hazardous Material.

## SECTION 15 - REGULATORY INFORMATION

California Proposition 65 statement: This product does NOT contain chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

Does not contain any chemicals subject to the reporting requirements of SARA Title III, Section 313 (40 CFR Part 372) above de minimis concentrations.

## SECTION 16 - OTHER INFORMATION

This document replaces the 1/2/2023 version. All Safety Data Sheets reviewed for composition and regulatory status.

The information contained in this Safety Data Sheet is based on data available to us from suppliers, and is believed to be true and correct; however, Conklin makes no warranty, express or implied, regarding the accuracy of this data or results obtained from the use of this product. Conklin and its employees assume no responsibility for injury or damage from the use of this product.