

## ACCLAIM® FSG

## Two Part Urethane Flashing and Seam Grade Sealant

**Technical Data:**

<b>Resin Type</b>	Urethane
<b>Color</b>	Gray
<b>Coverage</b>	100 lineal feet at a 1/4" bead, 50 lineal feet at a 1/2" bead
<b>Density</b>	10.5 lbs./Gallon
<b>Number of Coats</b>	1
<b>Open Working Time</b>	30 minutes
<b>Dry Time**</b>	1-2 Hours
<b>Total Solids (by weight) (by volume)</b>	As mixed 100% 100%
<b>Elongation</b>	350% (ASTM D-2370)
<b>Tensile Strength</b>	200 psi (ASTM D-2370)
<b>VOC Content</b>	0g/L (0.0 lbs./gal)

**Manufacturer:**

Conklin Company Inc.  
551 Valley Park Drive  
Shakopee, Minnesota 55379  
(800) 888 – 8838 Fax (952) 496 - 4285

**Product Description:**

**Basic use:** Acclaim® FSG is a two part urethane sealant for flashing and seams. Acclaim® FSG can be used prior to the application of Conklin's acrylic or urethane coating products for use over metal, BUR, modified bitumen membranes, PVC membranes, SPF, ISO board, wood, glass mat faced gypsum panels, and concrete.

**Limitations:** Must not be applied at temperatures below 40°F or during inclement weather. Surface temperature must be at least 5°F above dew point and relative humidity less than 80 percent to ensure dry surfaces. Mix thoroughly before use. Ambient temperature should not exceed 100°F and surface temperature should not exceed 120°F. Acclaim® FSG material must be 60°F or above to mix properly. The surface must be free of ponding water.

**Sizes:** Available in a 1/2 gallon kit. (4 pack)

**Coverage Rate:** Acclaim® FSG can be applied up to an inch thick in a single application. If greater thickness is required allow an hour between applications.

\*\*Dry time for Acclaim® FSG will vary depending on temperature, humidity, thickness at which the product is applied.

**Application:**

**Mixing/thinning:** Thoroughly mix the larger container of Part B (1 gallon container) to blend the powder and liquid. When mixed, Part B will be a thick paste. Then, pour the smaller container of Part A (1 quart container) into the larger container, and mix until uniform.

**Surface Preparation:** The substrate must be structurally sound, solid, clean and dry. On certain decks and surfaces, proper installation of drains, vapor retarders, roofing vents, expansion joints, flashings, and positive slope to drain will be required.

The application surface must be finished, smooth and free of grease, wax, dirt, contaminants, moisture and other matter that would interfere with adhesion. It must also be free of chips loose roofing or other foreign matter.

# ACCLAIM® FSG

## Two Part Urethane Flashing and Seam Grade Sealant

**Application:** For best results ensure surface is dry. Acclaim® FSG can be applied with a brush or spatula. Allow for 25 percent expansion. Apply Acclaim® FSG to the acceptable substrate. Allow Acclaim FSG to set up, and then coatings applied.

### Clean Up:

While coating is still wet, clean tools and the area with xylene.

### Disposal:

Dispose of product in accordance with local state and federal regulations governing hazardous waste.

### Safety:

**Warning:** HARMFUL IF SWALLOWED. May cause eye, skin and respiratory system irritation. Keep out of the reach of children. If spraying use a NIOSH-approved dust/mist mask.

**First Aid:** Eyes – immediately flush with plenty of water for at least 15 minutes. If a contact lens is present, **DO NOT** delay irrigation or attempt to remove the lens until flushing is complete. Skin – wash with soap and water, followed by a thorough rinse. Ingestion – if swallowed, **DO NOT INDUCE VOMITING**, dilute with three to four glasses of water. Immediately call a Poison Control Center or physician for further instructions. Inhalation – immediately move to fresh air.

For US Health Hazard Information, call:

**1-888-786-0974**

**Proposition 65 Statement:** This product contains chemicals known to the State of California to cause cancer.

### Storage:

Keep containers tightly closed when not in use. Store in a cool place, above 40° F. Keep from freezing.

**Please Note:** *Previous field- applied coatings and residential properties are not warrantable.*



©Conklin Company Inc. 2022  
09212022